



Two-color 3 inch Inkjet POS Printer

SRP-500

2-color

HIGHLIGHTS

- Fast print speed of up to 6.5 lps
- High resolution graphics
 - Print coupons, promotions, announcements, receipts, requisitions
 - Applications POS, kitchen printer, banking, kiosk, credit card authorization, data logging & measuring equipment etc.
- Choice of two color combinations black, red, blue, green
- Multiple interfaces
- Easy load cartridge
 - Inkjet technology by HP
- Instant ink feed
- No smearing or ink transfer
- Print head built into cartridge
- No degradation of print quality as with ribbons
- Uses low cost recycled paper

With this two-color inkjet POS printer, your customers draw the end user's attention to the slip as you can turn this dull piece of paper into a marketing revelation. Receipts and vouchers receive vibrant color with any application using the SRP-500. A low ink consumption results in lower ink cartridge expenses due to advanced ink management. With the SRP-500 you have both operating expenses and acquisition costs always under your control. A printing speed of 13 rows per second make the SRP-500 significantly faster than conventional dot-matrix printers and at the same time even more cost-effective. The proven and advanced HP ink dries instantly and offers high quality printing on low-cost paper. Retailers will find inkjet printing bright, clear, and crisp. With standard color selections including black, red, blue, or green, the SRP-500 offers enhanced versatility in printing graphic images, logos, coupons, rebates and specials.

SPECIFICATIONS

PRINT

- PRINTING METHOD : Inkjet
- PRINTING SPEED : 13 lps(at 12column) / 6.5 lps(at 40 column)
- RESOLUTION : Text 104 dpi x 96
Graphic 208 dpi x 96
- CHARACTER SIZE : Font A : 14 x 12 / Font B : 12 x 12
Korean : 24 x 12 / Chinese : 20 x 24
- CHARACTERS PER LINE :
Font A : 36 / Font B : 42, Korean : 21 / Chinese : 25
- CHARACTER SET : Alphanumeric Character : 95
Extended Character : 128 x 12 pages
International Character : 32
- BARCODES :
EAN-13, EAN-8, Code 39, Code 93, Code 128, ITF, Coda Bar, UPC-A, UPC-E

PAPER

- WIDTH : 76 ± 0.5mm
- PAPER ROLL DIAMETER : Max Ø 83mm
- PAPER LOADING : Easy Paper Loading

RELIABILITY

- PRINTER UNIT : 18 million lines
- AUTO CUTTER : 1.5 million cuts

INTERFACE : Serial(RS-232C) / Parallel (IEEE 1284) / USB

RECEIVE BUFFER : 8 Kbytes

NV IMAGE MEMORY : 256 Kbytes (Mono / Color)

EMULATION : BXL / POS

DRIVER : Windows, OPOS

SENSOR : No Cartridge Indicator, Paper Near End Sensor, Paper End Sensor, Front Cover Open Sensor

DRAWER PORT : 2 ports

POWER SUPPLY (SMPS) : AC 100-240V / DC 24V, 2.5A

DIMENSIONS : 172 x 226 x 152 (W x L x H mm)

OPERATING TEMPERATURE : 0-45°C

OPTION

- INK CARTRIDGE (RIC-500B/R/C/G)
- BIXOLON MELODIST (RMB-100)

**BIXOLON Co., Ltd.**

7-8th FL, Miraeasset Venture Tower, 685, Sampyeong-dong,
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, KOREA (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

BIXOLON America Inc.

3171 Fujita St Torrance,
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

BIXOLON Europe GmbH

Tiefenbroicher Weg 35,
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de