



## HIGH PERFORMANCE IN-COUNTER IMAGING SCANNER AND SCANNER/SCALE

The Magellan™ 9800i scanner/scale defines a new class of high performance bar code scanners for a worldwide market. With digital imagers in all planes, the 9800i scanner is the only scanner capable of reading both 1D and 2D bar codes seamlessly without requiring item orientation by the cashier.

The image capture power of multiple imagers also increases the first pass read-rate on all types of bar codes because it fills in the gaps left between laser lines. With the 9800i scanner, highly truncated, damaged or small element labels are scanned at full-sweep speed, providing maximum scanning throughput and a better bottom line.

The striking new design improves ergonomics with its lower bonnet height to allow repositioning of POS or Self-Checkout touchscreens, payment terminals and receipt printers to better accommodate ADA customers. The centered speaker provides audio feedback with .wav files for greater fidelity. The large horizontal window is ergonomically positioned for both standing and seated cashiers.

An integrated, customer-facing mobile device reader enables retailers to easily engage in mobile commerce. This eliminates the need for an additional scanner, power supply, outlet, interface cable, POS port and mounting hardware. The customer can scan bar codes from their mobile phone screen or paper coupons while the cashier continues to scan regular items in parallel, resulting in a significant reduction in total transaction time.

The 9800i scanner provides two scale options. First is the integrated 0.01 to 30.00 lb. capacity scale; second is an integrated high-resolution scale for low weight/high per lb. price items that provide additional revenue and higher profits.

Shrink reduction ranks high among retailers' concerns and the Magellan 9800i scanner has key features designed to reduce shrink at the POS. Long, variable-weight produce that does not easily fit on the scale platter introduces the opportunity for shrink to occur. Hurried cashiers regularly lay this long produce partially on the adjacent check stand and therefore do not capture the full weight. Datalogic's new ScaleSentry™ technology senses when this type of shrink event occurs and automatically alerts the cashier to take corrective action. Additionally, the 9800i scanner accommodates Checkpoint™, Sensomatic™ and Nedap™ EAS antennas and loss prevention software to reduce shrink and Failure to Deactivate (FTD) events.

Remote Management is supported for OPOS, JavaPOS, IBM™ Director and Wavelink™ Avalanche. Additional capabilities are available with the Value Added Features included in every Magellan scanner.

## FEATURES

- Advanced digital imaging in all reading planes
- Seamless reading of 1D and 2D codes in all planes with good-read audio and visual confirmation for fast, uninterrupted scanning
- Top Down Reader adds large topside field-of-view as well as a customer-facing mobile device reader
- The largest ever All-Weights™ scale platter enables effortless, accurate weighing of long or bulky items
- ScaleSentry™ Shrink Monitoring/Prevention System technology reduces losses from oversized items placed outside the weighing surface
- Low bonnet height allows for accessibility and flexibility in checkstand layout
- Top side accessible service port allows for the product to stay in the counter for most service calls (including software upgrades), reducing service and scale recalibration costs



## DECODING CAPABILITY

|                          |   |
|--------------------------|---|
| <b>1D / LINEAR CODES</b> | Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.  |
| <b>STACKED CODES</b>     | EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MicroPDF417; PDF417; UPC A/E Composites |
| <b>2D CODES</b>          | Aztec Code; Data Matrix; QR Code, Micro QR  |

## ELECTRICAL

|                              |   |
|------------------------------|---|
| <b>AC POWER REQUIREMENTS</b> | AC Input: 100 - 240 VAC, 50-60 Hz<br>Power Consumption: Operating (Maximum): TBD<br>Operating (Nominal): 12 Watts |
|------------------------------|---|

## ENVIRONMENTAL

|                                       |  |
|---------------------------------------|--|
| <b>AMBIENT LIGHT</b>                  | 0-86,080 lux   |
| <b>HUMIDITY (NON-CONDENSING)</b>      | 5 - 95%  |
| <b>ESD PROTECTION (AIR DISCHARGE)</b> | 25kV   |
| <b>TEMPERATURE</b>                    | Operating: 10 to 40 °C / 50 to 104 °F<br>Storage/Transport: -40 to 70 °C / -40 to 158 °F |

## INTERFACES

|                                       |  |
|---------------------------------------|--|
| <b>AUXILIARY PORTS</b>                | Powered RS-232 for handheld; Remote Scale Display; EAS Controller Ports; Sensormatic, Interlock; Powered USB Host (Type A) (x2)  |
| <b>MULTI-INTERFACE</b>                | IBM 46XX; USB Multi-Interface; OEM (IBM) USB; RS-232 (Scanner); RS-232 (Scale)/Single Cable RS-232   |
| <b>REMOTE MANAGEMENT CAPABILITIES</b> | Diagnostic Reporting; Diagnostic Report: WMI (OPOS and JavaPOS) and MBeans (JavaPOS) compliant<br>Host Download; Supports IBM Director, Wavelink Avalanche™ and other ERP management solutions |

## LOSS PREVENTION

|                                 |   |
|---------------------------------|---|
| <b>ALL-WEIGHS SCALE PLATTER</b> | Integrated horizontal and vertical scale platter surfaces increase active weighing area for easy, accurate weighing of large items.<br>ScaleSentry™ Shrink Monitoring/Prevention System (not available with Adaptive Scales); Configurable audio / visual indicators identify items placed outside weighing surface |
| <b>EAS FEATURES</b>             | System Support: Checkpoint Systems: Integrated EAS Antenna for Counterpoint IX and Evolve D11 models; Sensormatic: Datalogic SmartSentry™ Firmware technology interfaces with the Sensormatic AMB-9010/IPS EAS Deactivation Controller; (AMB-5120)<br>Good Read / EAS Status Indicators                             |

## OPTIONAL FEATURES

|                                  |  |
|----------------------------------|--|
| <b>MAGELLAN SCALE TECHNOLOGY</b> | Compatibility – Adaptive Scales: Avery; Bizerba; DIGI; Herbert; Mettler Toledo; Shekel<br>Max. Static Weight: 68.0 kg / 150.0 lb<br>Vibration Immunity: 4 Programmable Filter Settings |
| <b>DUAL INTERVAL SCALE</b>       | Minimum Increment: Range 1: 0.002 kg / 0.005 lb;<br>Range 2: 0.005 kg / 0.010 lb<br>Scale Capacity: Range 1: 0 - 6.0 kg / 0 - 13.2 lb;<br>Range 2: 6.0 - 15.0 kg / 13.2 - 30.0 lb      |
| <b>SINGLE INTERVAL SCALE</b>     | Minimum Increment: 0.005 kg / 0.010 lb;<br>Scale Capacity: 0 - 15.0 kg / 0 - 30.0 lb   |

## PHYSICAL CHARACTERISTICS

|                              |   |
|------------------------------|---|
| <b>DIMENSIONS</b>            | Depth (Below Counter): 10.6 cm / 4.0 in<br>Height (Above Counter): 6.8 cm / 2.7 in<br>Length: Model 9801 (Short, Scanner Only): 35.2 cm / 13.9 in<br>Model 9803/9804 (Medium, Scanner/Scale): 39.9 cm / 15.7 in<br>Model 9805/9806 (Long, Scanner/Scale): 50.7 cm / 20.0 in<br>Width: 29.2 cm / 11.5 in |
| <b>GLASS OPTIONS</b>         | Diamond-Like Carbon (DLC) Glass: High transmissivity glass optimized for imaging performance<br>Sapphire Laminated Glass: Lifetime Guarantee (optional)   |
| <b>INDICATORS</b>            | Audio: 85 dB Speaker; Adjustable Tone and Volume; Supports WAV file formats<br>Visual: Good Read confirmation for all reading planes; Scale center of zero ; ScaleSentry™ event; Sensormatic EAS status   |
| <b>TOP DOWN READER (TDR)</b> | Cast Aluminum Construction<br>Height: 30.5 cm / 12.0 in<br>Height: 17.8 cm / 7.0 in<br>Independent ON and GOOD READ indicators for TDR  |

## READING PERFORMANCE

|                         |  |
|-------------------------|--|
| <b>IMAGE CAPTURE</b>    | TDR: Graphic Formats: BMP, JPEG; Greyscale: 256, 16, 2   |
| <b>IMAGE SENSOR</b>     | Global Shutter 1.3 Megapixel (1280 x 1024) Monochrome CMOS Imagers (x4)  |
| <b>ILLUMINATION</b>     | Multiple Diffused LEDs: Orientation and wavelength optimized for eye comfort   |
| <b>MICROPROCESSORS</b>  | 5 Total: ARM Cortex A8 @ 800 MHz<br>Up to 4 Ghz total processing power in a fully loaded system (with TDR)<br>Up to 160 MB of RAM in a fully loaded system<br>2 GB of internal Flash |
| <b>READING COVERAGE</b> | ID/2D: 6 sides + customer facing module; Seamless reading of linear and 2D codes in all planes   |

## SAFETY & REGULATORY

|                                 |   |
|---------------------------------|---|
| <b>AGENCY APPROVALS</b>         | The product meets necessary safety and regulatory approvals for its intended use.<br>The Quick Reference Guide for this product can be referred to for a complete list of certifications. |
| <b>ENVIRONMENTAL COMPLIANCE</b> | Complies to China RoHS; Complies to EU RoHS; R.E.A.C.H. - EC1907/2006   |

## UTILITIES

|                       |   |
|-----------------------|---|
| <b>MAGELLAN™ OSP</b>  | Datalogic configuration program is available for download at no charge.   |
| <b>OPOS / JAVAPOS</b> | JavaPOS Utilities are available for download at no charge.<br>OPOS Utilities are available for download at no charge. |

## VALUE ADDED FEATURES

|                                      |   |
|--------------------------------------|---|
| <b>CASHIER TRAINING™</b>             | Identifies poor scanning habits by monitoring scan window usage, detecting excessive item orientation; Monitors dynamic weight to detect excessive lifting by cashier |
| <b>PRODUCTIVITY INDEX REPORTING™</b> | Captures label data statistics by cashier and lane;<br>Averages data to identify hard-to-read labels  |

## WARRANTY

|                 |                         |
|-----------------|-------------------------|
| <b>WARRANTY</b> | 1-Year Factory Warranty |
|-----------------|-------------------------|

## ACCESSORIES



11-0373: Remote Scale Display, Single Head



11-0375: Remote Scale Display, Dual Head