

Consumer appealing yet industry prooved

With Multitouch panel – optimized for displaying office documents



- Windows® Mobile® 6.5.3
- 3.7 inch capacitive multitouch display
- IP54 and 1.5 m drop resistance
- Pocket size - 215g light weight
- Consumer appealing yet industry prooved

Specifications		
Model		IT-300-15E
CPU		Marvell® PXA320 624MHz
OS		Microsoft® Windows Mobile® 6.5.3 English Version
Memory	RAM	256MB
	ROM	256MB (User area: Approx. 120MB)
Display	LCD	9.4cm (3.7 inches) VGA (480x640 dots) Blanview® Color LCD with Touch Panel
	Indicator	Indicator 1: Battery charging status Indicator 2: Wireless communication and scanning status
Input	Keyboard	Numeric (Alphabet) keys, CLR key, execute key, cursor keys, power key, Fn key, F1 to F4 keys, trigger Key
	Touch Panel	Yes (Capacitive type)
Scanner	Type	Semi-conductor laser
	Resolution	0.127mm
	1D	GS1 DataBar Omnidirectional, GS1 DataBar Truncated, GS1 DataBar Limited, GS1 DataBar Expanded, Code128/GS1-128 (UCC/EAN128), Code93, Code39, EAN8, EAN13, UPC-A, UPC-E, Codabar (NW-7), IATA, ITF, MSI, Industrial 2 of 5
	Stacked	GS1 DataBar Stacked, GS1 DataBar Expanded Stacked
Wireless LAN	Standard	IEEE 802.11b (Maximum: 11Mbps), IEEE 802.11g (Maximum: 54Mbps)
	Security	WPA2 / AES
Interface	Bluetooth®	Bluetooth® Version 2.0+EDR compatible
	Card Slot	microSD Memory Card (SDHC) x 1
	USB Port	Version 1.1 (Host/Client)
	Audio	Microphone: Built-in (monaural), Speaker: Built-in (monaural)
Power	Main Power	Lithium-ion battery pack (Operating period: Approx. 10 hours*) *Based on a ratio of „standby:calculation:scan:wireless communication“ of 20:1:1:1
	Memory Backup	Lithium battery (rechargeable) on board
Durability	Dust/Splash-proof	IP54 (compliant with IEC60529 standard)
	Drop Durability	1.5m
	Operating Temperature	-20°C to 50°C
Vibrator		Comes standard
External Dimensions (WxDxH)		76 × 155 × 19.6 mm
Approx. Weight		215g (Including lithium-ion battery pack)

