

MX8 Compact, Rugged Handheld Computer



HANDHELD COMPUTERS

Compact, lightweight ergonomic design for extended hours of comfortable use.

Standard-range and 1D and 2D bar code support.

Brilliant display and backlit keys designed for crystal-clear viewing even in dimly-lit areas.

Bluetooth® 2.0 + EDR for wireless peripheral support.

Removable, easy-grip handle with two-finger trigger and molded rubber grip for full-shift comfort.

Image capture for specialized materials management applications.



Choice of keypads:

- 32-key alpha-mode or
- 32-key alpha-numeric (right)

Multiple function keys with full, customizable keyboard mapping.



32-key alpha-numeric

Scan status vibration confirms good/bad scan even in the noisiest environments.

Voice-ready with ToughTalk™ technology to support your voice-directed warehouse applications.

LXE is_RUGGED MOBILE COMPUTERS.

Location, location, location

Ideal for a vast array of data-collection tasks: take the MX8 computer wherever you need it. From the rough neighborhoods of warehouse operations to the temperate climate of the retail storefront, the lightweight MX8 computer is right at home. It's engineered for all-day comfort yet tough enough to endure day-to-day operations. Best of all, this quality and durability is available at a great value.

The MX8 computer ships voice-ready with ToughTalk™ technology, a specialized combination of LXE's trademark rugged system design, advanced audio circuitry and noise-canceling techniques - for industrial-grade voice logistics applications.

Built like a tiny brick house and smart as a whip

Look beyond the tough, eye-catching body and you'll find enough power to support your various application needs. You'll fancy the Windows® CE operating system, high-performance processor, 802.11a/b/g radio and the latest Bluetooth® technology.

And the MX8 computer is supported by LXE's award-winning support team, winners of the Mobile Star Award™ for best customer service six years in a row.



MX8

Technical Specifications



Processing & Memory

- PXA270 520MHz
- 128MB SDRAM
- 128MB Flash
- 128MB, 512MB, or 1GB mini-SD card

Operating System

- Windows® CE 5.0
- Non-volatile storage of resident drivers, applications and settings

Optional Software

- RFTerm® (TN5250, TN3270, VT220)
- AppLock utility controls user application access & unwanted configuration changes
- Java Virtual Machine
- Multiple language OS support
- Voice recognition
- Wavelink Avalanche™ and LXE eXpress Config compatible

Application Development

- Free SDK available through LXE's Developer Portal - <http://www.lxe.com/developer>
- Sample code for each API call
- Complete example applications
- Developer-related FAQs

Keyboard

- 32-key alpha-mode and numeric-alpha keypad options
- Backlit keys
- Five dedicated function keys + user-defined function keys
- Full keyboard mapping support
- Abrasion resistance key coating

Display

- 2.8" (71mm) 240x320 QVGA TFT color LCD
- 300 NIT brightness
- Resistive touch screen with stylus

Power Supply & Management

- 3000mAh 3.7V Li-ion battery
- Full-shift battery life (w/typical usage)
- Backup battery w/automatic charging for main battery hot-swap
- Main battery low warning
- Configurable active power management

Interfaces

- USB Client
- RS-232
- Power for in-terminal charging
- Audio for headset, voice recognition application certified
- Speaker with adjustable volume control
- Large scan status LED
- Power status LED

Radio

- 802.11b/g, Wi-Fi certified radio
- 802.11a/b/g radio (Available Q4 2008)
- Internal diversity antenna
- WPA or WPA2 security
- Bluetooth® 2.0 + EDR

Enclosure

- Dimensions: 7.6" x 2.8" x 1.8" (193mm x 71mm x 46mm)
- Weight: 13.3 oz (377g) including radio, battery, and scanner

Environmental

- Temperature rating
Operating: 14°F to 122°F (-10°C to 50°C)
Storage: -4°F to 158°F (-20°C to 70°C)
- Humidity
Operating: 5% to 95% non-condensing at 104°F (40°C)
- Drop specification:
4ft (1.2m) multiple drops to concrete (w/handle)
- Tumble: 500, 0.5m
- Ingress protection enclosure rating: IEC 60529 compliant to IP54
- Vibration testing: Based on MIL STD 810F

Approvals

- Emissions (EMI)
FCC Part 15 Subpart B, Class A;
EN 55022, Class A (CISPR 22)
- Immunity (EMC)
EN 55024:1998
- Safety
UL 60950, CSA
C22.2 No. 60950,
EN 60950, IEC 60950
- Laser Safety
CDRH:21 CFR 1040.10,
EN 60825-1 and IEC 60825-1
- Radio
FCC Part 15C
Industry Canada RSS 210, 102
EN 300 328
- RoHS-compliant

Bar Code

- Standard range laser
- 1D and 2D Imagers
- Scan status vibration feedback and easy view scan LED

Accessories

- Trigger handle
- USB and RS-232 adapter cables
- Protective boot
- Desktop cradle with spare battery charging
- Passive vehicle cradle
- 4-slot battery charger
- Carry case for MX8 without handle
- Carry case for MX8 with handle
- Holster for MX8 without boot or handle
- Holster for MX8 with handle
- Holster for MX8 with boot and handle

