

Omni-Directional Imaging Scanner



Features:

- Aggressive imaging performance and intuitive operation reduces checker training and speeds checkout for better customer service
- Autodiscriminates PDF and 1D bar codes
- New imaging technology eliminates moving parts associated with laser scanners for improved reliability
- Targeted scanning mode for PLU Lists
- Hands-free scanning for small, easily handled items, handheld scanning for bulkier items
- Precise imaging scan volume eliminates misreads caused by stray laser scan lines
- Small footprint and size allow for easy integration into point-of-sale
- Textured rubber grip area and small size allow hands of all sizes to comfortably hold the scanner when needed
- Checkpoint® Systems EAS compatible
- Tilting stand allows scan volume to be optimized for each user and has screw holes for fixed mounting
- Standard product is available in either Black or Light Grey. Other colors and custom logo options are available for a minimum quantity purchase. Please contact Datalogic Scanning or your Datalogic Scanning reseller for more information on this service.

Data Sheet

Mechanical

Dimensions (Scanner with Stand):

Height: 7.13" / 18.1 cm Width: 3.23" / 8.2 cm Length: 3.82" / 9.7 cm Weight: 15.7 oz / 345.4 g

Environmental

Temperature Rating

Operating: 32° to 104° F / 0° to 40° C

Storage/Transport: -40° to 158° F /-40° to 70° C

Humidity: 5 to 95% NC (non-condensing)

Shock: Multiple 4' / 1.2 m drops Water & Dust Resistance: IP52

Electrical

Operating Voltages 5.0V model ± 5% 8.0 – 14.0V model

Operating Current (idle): < 350mA Operating Current (label read): < 450mA

Communications

- RS-232
 - 5-232 US
- OEM USB
- Keyboard Wedge
- Wand Emulation IBM 46xx / RS-485

Optical

Scan Pattern: 100 line

Scan Rate: 1,100 (digital scan lines/second)

Single Line Activation: via button Scan Volume: 80 in³ / 1311 cm³ Minimum Resolution: 5 mil Print Contrast: 25%

Roll: 0 – 360° Pitch: ±65° Yaw: ±75° Ambient Light

> Indoor: < 557 foot candles / 6,000 Lux Outdoor: < 7,999 foot candles / 86,100 Lux

Depth of Field: Please refer to table below

DEPTH OF FIELD

DEPTH OF FIELD	
Range Comparisons	
LABEL DENSITY	RANGE
5 mil	0.75 to 2.0" / 1.9 to 5.0 cm
6.6 mil (PDF)	1.5 to 3.0" / 3.8 to 7.6 cm
7.5 mil	0.5 to 4.0" / 1.3 to 10.2 cm
10 mil	0 to 6.0" / 0 to 15.2 cm
10 mil (PDF)	1.25 to 7.0" / 3.1 to 17.7 cm
13 mil (UPC)	0 to 8.0" / 0 to 20.3 cm
15 mil (PDF)	1.0 to 8.0" / 2.5 to 20.3 cm
20 mil	0 to 9.0" / 0 to 22.9 cm
Minimum distance determined by symbol length and scan angle.	

Printing resolution, contrast, and ambient light dependent.

Decoding Capability

The Magellan 1400i omni-directional imaging scanner autodiscriminates between the following supported symbologies:

Retail Codes:

- EAN 8 & 13 with full expansion 8 to 13
- EAN/JAN two label
- JAN 8 & 13 with full expansion 8 to 13
- UCC/EAN 128
- UPC Versions A&E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & C128)
- Dual Bar Codes for Japan (2 label read)
- Italian Pharmacode
- PDF-417/Micro-PDF
- Reduced Space Symbology (RSS): RSS-14, RSS expanded, RSS Stacked (omni-directional), RSS Composites and RSS Limited
- Supports GTIN

Industrial Codes:

- Code 39 (with full ASCII)
- Code 128 (Up to 80 characters, including Code 39 conversions)
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- Codabar
- MSI/Plessey

Please contact your Datalogic Scanning representative for other available symbologies.

Safety and Regulatory

Electrical: Gost R; TÜV; UL; cUL; NOM

Emissions: Complies to FCC; EN 55022; AS/NZS CISPR 22; VCCI; CNS 13438; ICES-003

Restriction of Hazardous Substances: Complies to FU RoHS



Other

EAS Compatibility: Integrated EAS hardware works with Checkpoint® Systems.



Datalogic Scanning, Inc.

Toll free: 1800 695 5700 International: 1541 683 5700

www.datalogic.com

E-mail us at: scanning@datalogic.com



Copyright © Datalogic Scanning Inc. 2005-2007. All rights reserved Protected to the fullest event under U.S. and international laws. Copying or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. - Datalogic Scanning, Inc. of Eugene, Origon, So. So. Decisiered by NQA.

- The Datalogic Organis a trademark of Datalogic SpA. - Magellan is registered trademarks of Datalogic Scanning Inc. - All other brand and product names are trademarks of their respective owners. - Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site www.datalogic.com - Product specifications are subject to change without notice.



Phone: 1-800-351-9962 Fax: 1-312-212-1800

About BarcodesInc

Who We Are

BarcodesInc is North America's leading provider of •] ^& \hat{a} \hat{a}

We Owe Our Success To You

Why Choose BarcodesInc?

Dedicated Account A UbU[Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

Highly-Trained Technical Support

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same & È

Premier Access to Top Manufacturers

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

Responsive Customer Service

Every phone call and email is responded to promptly, completely and accurately by our customer service & æ È

Easy Returns

Damaged, defective or incorrectly ordered goods may be returned without hassle.

BRANDS





Intermec

Honeywell

ODATALOGIC.











unitech





Microsoft*



symbol*

AND MORE