

## On-Counter Presentation Omnidirectional Bar Code Reader

The Magellan™ 800i omnidirectional presentation scanner is a versatile data collection tool for many applications. It uses Datalogic Scanning's latest digital imaging technology to provide intuitive and fast reading of 1D and 2D bar codes as well as supporting more advanced features like image capture and EAS tag deactivation. Despite its small size, the Magellan 800i reader provides big performance and reliability along with a rich feature set to provide excellent value in virtually any data collection system.

The Magellan 800i reader uses third generation Illumix™ intelligent illumination technology to optimize light levels for automatically reading bar codes from mobile phones and for capturing images. Illumix technology also provides incredible motion tolerance, exceeding other 2D scanning solutions, enabling both 'sweep' and 'presentation' style scanning techniques.

When space is limited but high performance is required, look no further than the Magellan 800i reader. Its compact size and footprint

make it the ideal solution for space-constrained environments. Its precise imaging scan volume is perfect for hands-free scanning in confined spaces and helps reduce accidental misreads of items caused by stray laser scan lines, improving productivity and customer satisfaction. For large, heavy or awkward-sized items, the Magellan 800i reader can easily be picked up for handheld use because of its small, ergonomic enclosure.

Like all Magellan bar code scanners, the Magellan 800i reader includes a powerful label editing tool which can parse or manipulate label data and also allows easy integration into existing or new host systems. The Magellan family of value added features (including Diagnostics Reporting, Host Download, and Advanced Label Editing) allow management to use valuable data from the scanner to improve throughput and manage maintenance. In addition, each Magellan 800i reader supports Remote Management Systems to streamline operations and ongoing support across an enterprise.

Improve your productivity and expand your data collection possibilities at the POS and beyond with the versatile Magellan 800i omnidirectional bar code reader.



## **Features**

- Aggressive performance on 1D and 2D codes increases productivity
- Powerful Advanced Data Editing for custom host output
- No moving parts for improved reliability
- Illumix™ intelligent illumination technology for reading bar codes from mobile phones or laptops
- Ergonomically designed for handsfree or handheld operation
- Small footprint for easy installation into space constrained applications
- Precise imaging scan volume eliminates misreads caused by stray laser scan lines
- Configurable image capture mode to optimize host upload time
- Checkpoint Systems EAS and Interlock compatible





# **\$DATALOGIC**

# Specifications

### **DECODING CAPABILITY**

1D / LINEAR CODES

2D CODES

STACKED CODES

**ELECTRICAL** CURRENT

INPUT VOLTAGE

**ENVIRONMENTAL** 

AMBIENT LIGHT DROP RESISTANCE

**ESD PROTECTION (AIR DISCHARGE) HUMIDITY (NON-CONDENSING)** PARTICULATE AND WATER SEALING **TEMPERATURE** 

**INTERFACES** 

**OPTIONAL FEATURES FAS FFATURES** 

**COLORS AVAILABLE** 

**VALUE ADDED FEATURES** 

PHYSICAL CHARACTERISTICS

DIMENSIONS WEIGHT

**READING PERFORMANCE** 

**IMAGE CAPTURE** PRINT CONTRAST RATIO (MINIMUM) **READING ANGLE** READING INDICATORS RESOLUTION (MAXIMUM)

**READING RANGES** 

TYPICAL DEPTH OF FIELD

complete list of certifications.

Complies to China RoHS; Complies to EU RoHS

UTILITIES MAGELLAN™ OSP

OPOS / JAVAPOS

REMOTE HOST DOWNLOAD

**SAFETY & REGULATORY** 

**ENVIRONMENTAL COMPLIANCE** 

AGENCY APPROVALS

WARRANTY

Autodiscriminates all standard 1D codes including GS1 DataBar™ linear

Aztec Code; Data Matrix; MaxiCode; QR Code

GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar

Stacked Omnidirectional; MicroPDF417; PDF417

Operating (Typical): < 350 mA Standby/Idle (Typical): < 250 mA

5 VDC (+/- 10%)

Indoor: 0 to 6,000 lux; Outdoor: 0 to 86,000 lux

Withstands repeated drops from 1.2 m / 4.0 ft onto a concrete

20 kV 5 - 95% IP52

Operating: 0 to 40  $^{\circ}\text{C}$  / 32 to 104  $^{\circ}\text{F}$ 

Storage/Transport: -40 to 70 °C / -40 to 158 °F

RS-232; USB: OEM USB, USB COM, USB HID Keyboard, USB TEC

Checkpoint Systems: Integrated EAS hardware will work with Counterpoint IV, V, VI and VII models

Sensormatic: Good Read Acknowledgement

Advanced Label Editing; Diagnostic Reporting; Host Download

Black; White; Other colors and custom logo options are available for

minimum quantity purchase. 15.1 x 7.6 x 10.9 cm / 5.9 x 3.0 x 4.3 in

306.2 g / 10.8 oz

Optional: 752 x 480 pixels; Graphic Formats: JPEG Pitch: +/- 60°; Roll (Tilt): 0 - 360°; Skew (Yaw): +/- 60°

Beeper (Adjustable Tone and Volume); Good Read LED 0.130 mm / 5 mils

Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

1D / Linear Codes

5 mils: 0 to 2.5 cm / 0 to 1.0 in7.5 mils: 0 to 8.2 cm / 0 to 3.2 in 10 mils: 0 to 12.7 cm / 0 to 5.0 in 13 mils UPC: 0 to 15.2 cm / 0 to 6.0 in 2D Codes

6.6 mils PDF417: 0 to 7.6 cm / 0 to 3.0 in 10 mils Data Matrix: 0.6 to 3.1 cm / 0.2 to 1.2 in 10 mils PDF417: 0 to 12.7 cm / 0 to 5.0 in

15 mils PDF417: 0 to 15.2 cm / 0 to 6.0 in 24 mils Data Matrix: 0 to 12.7 cm / 0 to 5.0 in

The product meets necessary safety and regulatory approvals for its

The Quick Reference Guide for this product can be referred to for a

Magellan On-Screen Programming (OSP) configuration software is available for download at no charge.

JavaPOS Utilities are available for download at no charge. OPOS Utilities are available for download at no charge. Lowers service costs and improves operations.

3-Year Factory Warranty



Integrated stand tilts at +60°/-15° angles for optimal reading



Base can be secured to a counter or wall for fixed applications

© 2011 Datalogic Scanning Inc. • All rights reserved. • Protected to the fullest extent under U.S. and international laws.

Copying or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc.

Datalogic and the Datalogic logo are registered trademarks of Datalogic S.p.A. in many countries, including the U.S.A. and the E.U.

Magellan is a registered trademark of Datalogic Scanning, Inc. in many countries, including the U.S.A. and the E.U.

Other brand and product names may be trademarks of their respective owners.

Product specifications are subject to change without notice.

www.scanning.datalogic.com



Phone: 1-800-351-9962 Fax: 1-312-212-1800

## About BarcodesInc

#### Who We Are

BarcodesInc is North America's leading provider of •] ^&  $\hat{a}$   $\hat{a}$ 

#### We Owe Our Success To You

## Why Choose BarcodesInc?

## Dedicated Account A UbU[ Yf

Our Account Managers will not compromise when it comes to providing you top-notch service. Your Account Manager is the primary point of contact for your business and makes it a priority to get to know you, your company and all your needs.

### **Highly-Trained Technical Support**

Our technical staff has the broadest knowledge and every significant certification in the industry. One of our friendly experts is always available to suggest products and solutions for any situation.

## Incredible Value

Our purchasing power means big savings for you. Whatever your project, our team will work hard to deliver a solution that fits your budget.

#### Largest Inventory in the Industry and Same-Day Shipping

Whatever your barcoding, mobile computing, or printing needs, we will fill your order and ship it the same & È

#### **Premier Access to Top Manufacturers**

BarcodesInc maintains strong strategic partnerships with the leading manufacturers in barcoding, mobile computing, printing and RFID.

## **Responsive Customer Service**

Every phone call and email is responded to promptly, completely and accurately by our customer service & æ È

## **Easy Returns**

Damaged, defective or incorrectly ordered goods may be returned without hassle.

### **BRANDS**





Intermec

Honeywell

ODATALOGIC.











unitech





Microsoft\*



symbol\*

AND MORE