

# SCP700 Series

Thermal Receipt / Label & Impact Slip Combination Printer






- Versatile two station printer combining thermal receipt / label and impact slip technologies
- Cost effective, fully capable POS printer
- Prints high quality thermal receipts or labels at up to 16.7 lines per second
- Small footprint occupying minimal counter space
- Impact slip station for the printing or validation of cheques, credit card forms, restaurant slips and other multi-part documents
- Flexible dual interface option for multiple system configuration

## Typical Applications

- **Pharmacy Printer**  
Unique compact printer able to simultaneously print labels and prescriptions
- **POS Printer**
- **Label / Slip Tracking**  
The SCP700 can be used in any environment where slips and / or labels need to be printed for product tracking – technical warranty departments etc.

**SCP700** Stand Alone Printer Unit



## SCP700 Printer Specifications

Standard Interface	RS232C (D-Sub 9pin)	Number of Dots / Line	576 Dots
Support Interfaces	Customer Display, Dual Cash Drawer Driver	Font, Character Size	12 x 24 / 8 x 24
Optional Additional Interface	RS232C (D-Sub 25 pin) or Centronics Parallel Interface	Printable Width	72mm
Power Requirement	24V DC / 2A, Connector Type TCS7960 53-2010 (HOSIDEN)	Paper Width	80mm
Agency Approval	UL, C-UL, FCC Class A, TÜV, CE	Paper Diameter	85mm
Dimensions / Weight	182 (W) x 270 (D) x 194 (H) mm, 3.5Kg	Paper Thickness	0.06 to 0.85mm
Operating Environment	5°C to 35°C, 25% to 85% RH (w/o condensation)	Core Diameter	Inner 12mm ± 1 / Outer 17mm ± 1
<b>SLIP PRINTER</b> – see SP298		Paper Feed Method	Stepping Motor
<b>THERMAL RECEIPT / LABEL PRINTER:</b>		Paper Feed Speed	50mm / sec.
Command Emulation	Star Mode, EPSON™ TM-T85	Sensor	Paper Out, Near End (3 Adjustable Positions)
Bar Code	UPC-A/E, EAN, ITF, CODE39, CODE128, CODABAR (NW7)	Autocutter Type	Full or Partial Cut
Print Method	Direct Linear Thermal	Reliability	10 million lines MCBF 38 million lines Calculated Real Time MCBF
Print Head	Linear Thermal Head	Print Head Life	50km
Horizontal Dot Pitch	8 Dots / mm (203 dpi)	Autocutter MCBF (Guillotine)	300,000 cuts (Full or Partial Cut) Label Version Full Cut only
Vertical Dot Pitch	8 Dots / mm (203 dpi)	<b>Interface Card (optional)</b>	
Print Speed	16.7 lines / sec. (50 / sec.)	IFBD-D Connector Type	RS232C
Number of Columns	48 (12 x 12 font), Font A 64 (9 x 24 font) (EPSON™ TM-T85 Mode only), Font B	IFBD-C Connector Type	D-Sub 25 Pin Centronics Parallel Amphenol Type 36 Pin Connector