





OTSP043 Series

NEW Low Cost, High Speed, Quality Printer Series

With its robust design and lever-free paper loading, this printer is designed to perform in the harshest of retail and hospitality environments. Its high speed processing of receipts (up to 250mm/second) as well as dual interface make it the first choice for retailers and hospitality operators globally.

- "Intelligent" Design
- Low cost Installation
- Low cost Maintenance
- 10cm diameter Paper Roll capacity
- Superior Quality Hardware & 203 dpi Output
- ESC/POS[™] emulation with *StarPRNT* Intelligence & Configuration Utility
- Advanced Splash / Dust Proof design



OTSP043 Series

NEW Budget, High Performance, Low Cost Receipt Printer designed specifically to meet basic receipt printing needs.

"Intelligent" Star Design with advanced splash-proof design – even the PCB is mounted upside down to maintain higher reliability than our competitors.



Compact, Easy-Load "Drop-In & Print" with lever-free paper loading to increase reliability.

Low cost installation Dual interface USB / Serial or USB / Parallel models.



TSP043UC GRY – Grey USB / Parallel TSP043UD GRY – Grey USB / RS232 White versions available on request.

StarPRNT Intelligence includes:

- · Advanced logo store
- "Text-Triggered" image printing perfect for couponing
 See website for more details.

ESC/POS™ emulation with Star Configuration Utility including OPOS™ and Epson cash drawer compatibility.

No dip switches.

All-inclusive *StarPRNT* driver and utility suite with WHQL certification on CD in box.



Low cost maintenance PS60 power supply can be included in box.

Low cost replacement of print head, cutter and PCB. Simply remove the front printer cover to access the cutter and print head or black plate to access the main printer circuit board (PCB).







TSP043 Specifications Print Method Direct Line Thermal Printing **Print Resolution** 203 dpi Speed: TRUE Print Speed Up to 250mm/second Paper Feed Speed Up to 300mm/second Software Control: Logo Store Epson compatible - up to 512kB / 9,025 logos (new) ESC/POS™ **Emulations** Code pages 40 + 1 blank **Dual Interface** USB / Serial 25pin or USB / Parallel Windows Driver ESC/POS™ with StarPRNT Intelligence & config utility Windows XP SP3, Vista 32/64 SP2, 7 32/64 None SP/SP1 Drivers available No Star Line mode available Character Size / Line Spacing Font A: 12 x 24 / Font B: 9 x 24 / Font A: 42 / 48 (80mm), 30 / 33 (58mm) Font B: 56 / 64 (80mm), 40 / 45 (58mm) (Selectable by Memory Switch) Vertical 50%, Horizontal 67% (by Firmware) Compressed Print Barcodes 1D x 9 versions / 2D - PDF417 Paper Specifications: Width 58 / 80mm (80mm default with 58mm guide) Printable Width 64mm / 45mm (72mm / 50.8mm Selectable by Memory Switch) Roll Diameter up to 102mm **Thickness** 0.065 ~ 0.085mm (0.057 ~ 0.065mm special paper only) Top Margin Approx. 11mm Standard Photo PE sensor; Sensors Optional Black Mark Sensor; Optional Paper NE Sensor **Power Supply** PS60A (External Type) Input / Supply Voltage 100V (-10%) to 240V (+10%) / 24V DC Reliability 60 million lines MCBF Auto-Cutter Partial Cut (One-Point Center) / Guillotine Type Min. Cut Length 24mm (0.065mm ≤ paper thickness ≤ 0.085mm) Auto-Cutter Life 1 million cuts Print Head Life 100 Km (using recommended paper) Additional Information: Simplified Tear-Bar Supported

GB18030 or Big 5

142 (W) x 212 (D) x 149 (H) mm

10cm diameter Paper Roll capacity

Unique 10cm outside diameter paper roll capacity with 60% more paper on a roll which means fewer paper roll changes; decreased cost per receipt; reduced paper roll transport and storage requirements.

Character Rom

Dimensions

No other manufacturer can offer all this!

STAR 10cm ROLL PAPER SAVING ADVANTAGES		
Paper Width	80mm	80mm
Outside Diameter	79.5mm	101mm
Core Size	12.7mm	12.7mm
Paper Thickness	65 microns	65 microns
Length of Paper on Single Roll	74m	124m
Increase over Standard Roll	0%	67.5%

