

star[✦] TSP654SK

The liner less, variable length alternative to traditional labelling



High performance, entry-level direct thermal printer

- ✦ **Low cost, liner less, variable length "Re-Stick" label solution which can be repositioned as required.**
- ✦ *The thermal 'Post-It™' note solution for the POS market.*
- ✦ **Environmentally friendly labelling with increased percentage of labels available per roll when compared to traditional methods**
- ✦ **Perfect for customer product labelling for food take-out, Pizzerias, Coffee shops, promotional couponing, fast food special orders etc.**

The TSP654SK liner-free printer is designed to work with liner-free labelling applications. Re-positionable thermal labels can stick to and be restuck to any surface and can be removed easily without leaving behind any residue. The liner-free labels are an alternative to using silicone-lined labels or tape.

The lack of a silicone liner eliminates the negative environmental impact of labelling & helps reduce in-house waste, thus continuing Star Micronics Global Green Initiative, which encompasses all its manufacturing products to ensure the least possible impact on our environment.




Vertical mount kit, 58mm guide, power switch cover & Installation CD included in box at purchase.

Interchangeable interfaces




Moulded desk boot for vertical use with graphics facility




Splash proof cover with easy paper loading

Power switch cover included in box











TSP654SK Specifications

Printer Method	Direct Thermal Line Printing
Print Speed	up to 150mm/second
Print Resolution No. of Columns	203 x 203 dpi 48 / 64
International Code Pages	Star Mode=40. ESC/POS™= 6 + 1 blank allowing an additional character page to be added
Barcodes	9 versions / PDF417 option
Emulation Logo Store capacity Flash ROM	Star Line Mode & ESC/POS™ 2 Mbit Flash ROM with graphic management 16 Mbit
Interface	Interchangeable Serial, Ethernet, Parallel or USB
Peripheral Drive Circuit	2 circuits (24V max, .1A) 1 compulsion input
Paper Width	80 mm standard / 58mm with guide
Easy Load	"Drop-In" & Print
Label Support	MAXStick Thermal liner free labels
Cover Open Sensor	Standard
Reflective Black Mark Near End Sensor	Standard 4 positions
Print Width	Max. 80mm wide
Top Margin	13mm default / 11mm selectable
Power Supply (External)	24 V Star PS60A-24 option
Dimensions (w x d x h) mm Weight Reliability Printer Print Head Autocutter	142 x 202 x 132mm 1.72 Kg 60 million lines 100 Km 1 million cuts (Guillotine partial cut only)
Included with Printer	Installation CD with drivers & configuration utility, wall mount bracket, vertical mount kit, 58mm paper guide, power switch cover, set-up guide, start up paper roll
Options	Splash proof cover (SPC-T100) Display stand for vertical use (VS-T650) Interchangeable interfaces Power supply PS60



POS PRINTERS

ALWAYS AT YOUR SERVICE.

TSP654SKUK 2/12